

Partslist and mounting instruction

Order No.: 6199 BR HD Breakout schwarz
 glänzend

Article: Solo Rack Ø 16 curved
 Black shiny

1 Solo-Rack

- 1 x Partslist and mounting instruction
- 1 x Label max. load 5 kg

Mounting parts front:

- | | | |
|---------------------|----------|-----|
| 1 x Mounting holder | | |
| 2 x Washer | DIN 9021 | M 6 |
| 2 x Cap safety nut | DIN 986 | M 6 |

Mounting parts rear:

- | | | |
|--------------------------------|-------------|----------------|
| 1 x Hexagon socket head screw | ISO 7380 | M 8 x 30 mm |
| 1 x Washer | DIN 125 | M 8 |
| 1 x Hexagon nut (self-locking) | DIN 985 | M 8 |
| 1 x Distancetube | | 18 x 4 x 10 mm |
| 1 x Washer | DIN 9021 PA | M 8 |



Photo 6198

Mounting instruction:

- Remove the passenger seat and remove the threaded cage.
- Remove driver seat.
- Unscrew the plastic washers from the driver's seat mounting holder.
- From the underside of the fender, replace the mounting holder with ours.
- Slide on plastic washers, fit solo-rack and seat.
- For the rear attachment, place the plastic washer on the fender and attach the spacer tube.
- Mount the passenger solo-rack with the listed mounting parts.

Care and servicing:

To reach a long live span of our chromium-plated articles they should be cleaned regularly and be treated with customary chrome care means.

With powder coated articles a regular cleaning is important. Damages (e.g. by rockfall) can be mended with colour.

By both versions we recommend about the winter the spraying or rubbing with corrosion protection oil or silicone.

All fixing bolts must be checked at regular intervals (max. 6 months).

We wish you a lot of joy and accident-free journey with our motorcycle accessories.

Datum/Name	Erstellt	Geändert	Geprüft Entwicklung	Geprüft Verkauf	Freigabe
	20231128 PK				