

Partslist and mounting instruction

Order No.: 6255 BR HD Softail Street Bob,
 schwarz

Article: Solo-rack Ø 16, curved, black

Fits for: Harley Davidson Softail Street Bob (Milwaukee-Eight 107/114), (FXBB) 2018-

1 Solo-rack

- 1 x Partslist and mounting instruction
- 1 x Label max. load 5 kg

Mounting parts front:

- | | | |
|-------------------------------|----------|-------------------------|
| 1 x Hexagon socket head screw | DIN 912 | 1/4" UNC x 7/8" (22 mm) |
| 1 x Washer | DIN 9021 | M 6 |

Mounting parts rear:

- | | | |
|-------------------------------------|------------|-------------|
| 1 x Hexagon socket round head screw | ISO 7380 | M 8 x 16 mm |
| 1 x Washer | DIN 125 | M 8 |
| 1 x Cap head safety nut | DIN 986 | M 8 |
| 1 x Washer | DIN 125 PA | M 8 |



Photo 6255

Datum/Name	Erstellt	Geändert	Geprüft Entwicklung	Geprüft Verkauf	Freigabe
	2020-03-18 PK				

Mounting instruction:

- Remove driver's seat retaining screw.
- Remove the original plug from the rear attachment.
- Slide the solo-rack between the threaded bush and the seat at the front attachment point.
- For the rear attachment, the screw is pushed through the mudguard from below and screwed tight from above with the cap nut.
- The polyamide washer is fitted between the solo-rack and the mudguard.
Fit the solo-rack with the mounting parts listed below, align and screw everything tight.
- Torques for bolts and nuts like from the manufacturer given
If not given: 4 M: 3 Nm - M of 5: 5,9 Nm - M of 6: 10 Nm - M of 8: 25 Nm - M of 10: 49 Nm - M of 12: 85 nm).
- Mount the screws, if necessary, with liquid screw protection.

Care and servicing:

To reach a long live span of our chromium-plated articles they should be cleaned regularly and be treated with customary chrome care means.

With powder coated articles a regular cleaning is important. Damages (e.g. by rockfall) can be mended with colour.

By both versions we recommend about the winter the spraying or rubbing with corrosion protection oil or silicone.

All fixing bolts must be checked at regular intervals (max. 6 months).

We wish you a lot of joy and accident-free journey with our motorcycle accessories.